

**Features**

- Full motion CCTV video at long distance(Max. 9,000ft/3000M).
- Built-in linearity, Sharpness and Chroma control
- Enable unparallelled common interferences rejection
- Built-in transient Protection.
- Improve the picture definition when connect to DVR or Quad, and reduce noise affects .

**Applications**

There are two kinds of video balun transceivers. One is Active and the other is Passive. According to different transferring distance , Please refer to the system selection chart below:

Nos of Cam.	Max Distance(ft)		Transmitter	Receiver	Remarks
	BW	Color			
1	1800	1200	LLT201A/C	LLT201A/C	No power required
1	6600	4800	LLT201A/C	LLT301R LLT351R LLT302R	DC 12V
1	8400	6600	LLT301T LLT351T LLT302T	LLT301R LLT351R LLT302R	DC 12V
4	6600	4800	LLT201A/C	LLT401R	DC 12V
4	8400	6600	LLT301T LLT351T LLT302T LLT401T	LLT401R	DC 12V
> 4	6600~ 8400	4800~ 6600	LLT201A/C LLT301T LLT351T LLT302T LLT401T	LLT301R LLT351R LLT302R LLT401R LLT610R	DC 12V 1610R AC 220V

- Use UTP CAT5 24AWG to measure the transferring distance in above chart .

Max:1200ft(Color)/1800ft(BW)UTP video transceiver



Max:4800ft(Color)/6600ft(BW)UTP video transceiver

