

Model	GSD-804P
<b>Hardware Specification</b>	
Network Connector	8-Port RJ-45 for 10/100/1000Base-T
PoE Inject Port	4-Port with 802.3af PoE injector function, Port-1 to Port-4
LED Display	1 Power , 1 FAN Alert 1-4 port PoE in-use 1-8 port Speed, LNK/ACT
Switch Architecture	Store and Forward switch architecture
MAC Address	8K MAC address table with Auto learning function
Switch Fabric	16Gbps
Switch Throughput	11.9Mpps
Jumbo Packet Size	9K Bytes
Power Requirement	AC 100~240V, 50/60Hz, 1.5A
Power Consumption	Max. 65 Watts / 221 BTU
Dimension (W x D x H)	217 x 135 x 43 mm
Weight	890g
<b>Power over Ethernet</b>	
PoE Standard	IEEE 802.3af Power over Ethernet / PSE
PoE Power Supply Type	End-Span
PoE Power Output	Per Port 48V DC, 350mA . Max. 15.4 Watts
Power Pin Assignment	1/2(+), 3/6(-)
PoE Power Budget	55 Watts
<b>Standard Conformance</b>	
EMI Safety	FCC Class A, CE
Operating environment	0 ~ 50 Degree C
Storage environment	-40 ~ 70 Degree C
Operating Humidity	5 ~ 95%, relative humidity, non-condensing
Storage Humidity	5 ~ 95%, relative humidity, non-condensing
Standard Compliance	IEEE 802.3: Ethernet IEEE 802.3u: Fast Ethernet IEEE 802.3ab: Gigabit Ethernet IEEE 802.3x: Flow Control IEEE 802.3af: Power over Ethernet